

Wireless Pathway Lighting Controls

Contact the team

Luke Arter	luke@tridonicdist.co.uk
Kevin Purcell	kevinpurcell@tridonicdist.co.uk
Ryan Grout	ryan@tridonicdist.co.uk



Pathway illumination simplified with Tridonic's basicDIM Wireless Outdoor Node.

Tridonic is committed to offering control solutions that are straightforward yet fully featured. A commonly underestimated application in our experience is pathway lighting.

Pathway lighting control becomes effortless with the BDW OTD node and the integration of various sensors within the BDW ecosystem. This approach guarantees energy savings and complete control, all manageable via your smartphone or tablet.



Features and benefits:

Wireless Control

Simple control via mobile devices or wireless switches.

Easy Installation

Zhaga book 18 socket for simple, all-weather installation (IP67).

Versatile Control

With the range of over 150m node to node, this enables you to manage single fixture to whole mast with multiple fixtures.

Custom Scenes & Controls

Utilise the inbuilt photocell to initiate the dusk to dawn energy saving feature from the BDW OTD node switch groups and scenes to control different lighting levels for different sections along pathways.

BDW Product Ecosystem

Utilise Zhaga Book 18 sockets with Tridonic's P sensor and the BDW ecosystem to create a secure and well-illuminated space with motion path capabilities. This not only enhances safety but also reduces energy consumption.

Product description

- _ Can be integrated in Casambi systems (Casambi Ready).
- _ Wireless controllable with an Android / iOS smart device.
- _ No need for an external gateway device.
- _ Forms automatically a wireless communication network with up to 250 nodes.
- _ Digital output to control IEC 62386 compatible drivers.
- _ Supplied via IEC 62386 compatible power supply.
- _ Support for Tridonic PSensor and MSensor.
- _ Ready for Zhaga book 18 receptacle for easy and flexible installation to luminaire.
- _ Device firmware can be updated over-the-air.
- _ Can be used as repeater to extend the coverage of the wireless signal.
- _ Lifetime up to 100,000 h at $t_c = 72^\circ\text{C}$.
- _ 5 year guarantee (conditions at www.tridonic.com)